



SOLARATOR SERIES

Experience Uninterrupted Power with Solis Energy Storage Inverters

S6-EH3P(29.9-50)K-H-AU

Three Phase | High Voltage

6 Leading Features

- Support flexible PV connection through DC and AC coupling simultaneously
- Support battery reserve function in multiple scenarios
- Smart Load Prioritizing – Extended support for critical loads
- Seamless on grid/off grid switching time <10ms
- Support max 10 pcs in parallel mode, >6 pcs recommend Solis power distribution cabinet
- SMARTLOAD/GEN/INV port - Flexible connection of multiple energy sources such as Grid-tied inverter, diesel generator, wind turbines, etc.

8 Unique Features

- Usable PV power up to 200% inverter rated power, improve the utilization of PV generation
- Support max 20A PV input current, perfectly match high power PV modules
- Compatible with 100-280Ah battery modules
- Support faster charging with battery current up to 140A
- Powerful backup overload capability – 160% overload
- Support wide power range of generator interaction from 10kVA to 50kVA
- Support 2 independent batteries connection for flexible configuration
- 7-inch large screen uses U.S.-made ZEITLER industrial-grade components

AUSTRALIA

t: +61 1800928995 e: sales@solisinverters.com.au w: solisinverters.au
+61 3 8555 9516 service@solisinverters.com.au



DATASHEET

S6-EH3P(29.9-50)K-H-AU

Models	29.9K	30K	40K	50K
Input DC (PV side)				
Recommended max. PV array size	59.8 kW	60 kW	80 kW	100 kW
Max. input voltage			1000 V	
Rated voltage			600 V	
Start-up voltage			180 V	
MPPT voltage range			150 - 850 V	
Max. input current	40 A / 40 A / 40 A			4 × 40 A
Max. short circuit current	45 A / 45 A / 45 A			4 × 45 A
MPPT number / Max. input strings number	3 / 6			4 / 8
Battery				
Battery type			Li-ion	
Battery voltage range			150 - 800 V	
Max. charge / discharge power	32.1 kW	33 kW	44 kW	55 kW
Max. charge / discharge current			70 A × 2 ⁽¹⁾	
Number of battery ports			2	
Max. charge / discharge power of each input	32.1 kW	33 kW	35 kW	35 kW
Communication			CAN / RS485	
Output AC (Grid side)				
Rated output power	29.9 kW	30 kW	40 kW	50 kW
Max. apparent output power	29.9 kVA	30 kVA	40 kVA	50 kVA
Rated grid voltage			3/N/PE, 230 V / 400 V	
Rated grid frequency			50 Hz	
Rated grid output current	43.2 A	43.3 A	57.7 A	72.2 A
Max. output current	43.2 A	43.3 A	57.7 A	72.2 A
Power factor			> 0.99 (0.8 leading - 0.8 lagging)	
THDi			< 3%	
Input AC (Grid side)				
Max. AC passthrough current	86.4 A	86.6 A	115.4 A	144.4 A
Rated input voltage			3/N/PE, 230 V / 400 V	
Rated input frequency			50 Hz	
Input Generator				
Max. input power	29.9 kW	30 kW	40 kW	50 kW
Rated input current	43.2 A	43.3 A	57.7 A	72.2 A
Rated input voltage			3/N/PE, 230 V / 400 V	
Rated input frequency			50 Hz	
Output AC (Back-up)				
Rated output power	29.9 kW	30 kW	40 kW	50 kW
Max. apparent output power			1.6 times of rated power, 2 s	
Back-up switch time			< 10 ms	
Rated output voltage			3/N/PE, 230 V / 400 V	
Rated frequency			50 Hz	
Rated output current	43.2 A	43.3 A	57.7 A	72.2 A
THDv (@linear load)			< 2%	
Efficiency				
Max. efficiency			97.8%	
EU efficiency			97.4%	
BAT charged by PV max. efficiency			98.5%	
BAT charged / discharged to AC max. efficiency			97.5%	
Protection				
Anti-islanding protection			Yes (Active frequency shifting)	
Output over current protection			Yes	
Short circuit protection			Yes	
Integrated DC switch			Yes	
DC reverse-polarity protection			Yes	
Surge protection			DC Type II / AC Type II	
Integrated AFCI 2.0			Optional	
Protection class / Over voltage category			PV II, battery II, AC III	
General Data				
Dimensions (W × H × D)			530 × 880 × 290 mm	
Weight			73 kg	
Topology			Transformerless	
Self-consumption (night)			< 35 W	
Operating ambient temperature range			-25 ~ +60°C	
Relative humidity			0 - 95%	
Ingress protection			IP66	
Cooling concept			Intelligent fan-cooling	
Max. operation altitude			4000 m	
Grid connection standard			AS/NZS 4777.2:2020	
Safety / EMC standard			IEC 62109-1/-2, IEC 61000-6-2/-4	
Features				
PV connection			MC4 Quick connection plug	
Battery connection			Terminal connector	
AC connection			Terminal Block	
Display			7.0" LCD display & Bluetooth + APP	
Communication			CAN, RS485, Ethernet, Optional: Wi-Fi, Cellular, LAN	
Country of manufacture			China	

(1) Supporting parallel 140A input.